CPI®-4126 Series

Air Compressor Lubricants



Description

The **CPI®-4126 Series** compressor lubricants are formulated using high quality diester base fluid combined with an excellent performance antitiwear additive package.

These compressor lubricants feature excellent thermal and oxidative stability, enabling them to operate over a wide range of temperatures without varnish, sludge, or carbon deposit formation. These products also feature excellent antiwear protection and low volatility, enabling decreased maintenance and reduced lubricant consumption.

The **CPI®-4126 Series** fluids are particularly suited for use in reciprocating and rotary vane compressors where high temperatures are prevalent.

Applications and Compressor Type

- Reciprocating compressors
- Rotary vane compressors
- Vacuum pumps
- Other applications requiring an oxidatively and thermally resistant lubricant

Features and Benefits

Oxidatively stableLonger system lifeLow volatilityReduced maintenance and top-offsExcellent lubricityIncreased efficiency, reduced cost of operation



Typical Properties*

Test Procedure	ASTM Test Method	CPI®-4126-100	CPI®-4126-150
Kinematic Viscosity, cSt	D445		Ì
40°C		100.8	150.7
100°C		10.96	14.53
Viscosity Index	D2270	92	94
Density, g/mL	D4052		
15.6°C		0.9380	0.9347
20.0°C		0.9351	-
Flash and Fire Point, °C	D92		
Flash Point		241	240
Fire Point		285	288
Pour Point, °C	D97	-42	-41
Demulsibility	D1401		
Water-Oil-Emulsion (Time, min.)		41-39-0 (15)	42-38-0 (10)
Copper Strip Corrosion	D130	1B	1B
Noack Volatility, % Loss	D5800		
200°C		0.8	1.0
Carbon Residue, %	D189	0.01	0.01

^{*}These values are not intended for use in preparing specifications

CPI Fluid Engineering www.cpifluideng.com

North and South America

The Lubrizol Corporation 2300 James Savage Road Midland, MI 48642, USA

Telephone: 1 (989) 496-3780 Email: sales@cpifluideng.com

Europe, Middle East and Africa

Lubrizol Limited Pavilion One, Belasis Court Greenwood Road Stockton-on-Tees TS23 4AZ, UK

Telephone: +44 1642 565266 Email: euafricamesales@cpifluideng.com

Asia-Pacific

Lubrizol Southeast Asia (Pte) Ltd 44 Tanjung Penjuru Singapore 609032

Telephone: + 65-66638 684 Email: asiasales@cpifluideng.com

