



The Ultimate Lubricant

# 615



Nonfood Compounds  
Category Code : H1  
Registration Number : 130634

## ULTRA HIGH-PERFORMANCE AIR ( & REFRIGERATION ) COMPRESSOR OIL:

Based on advanced synthetic chemistry, Omega 615 provides a new performance "envelope" for compressors (including refrigeration-types) unmatched by ordinary lubricants. Its special PAO (polyalphaolefin) blend, and anti-oxidant, rust inhibited, and anti-foam formulation provides this special lubricant with unmatched performance characteristics in rotary screw-and rotary vane-type compressors, using the ISO VG 46 grade; and in conventional reciprocating compressors, using the ISO VG 100.

Omega 615 provides unparalleled oxidation stability under extended, real-world operating

conditions. Ordinary compressor oils, due to their unstable characteristics, progressively thicken, alter their viscosity characteristics and tend to corrode surfaces coming into contact due to the tendency to increase in Total Acid Number (TAN).

Omega 615, on the other hand, is exceedingly oxidation-resistant and leaves no harmful deposits of varnish and carbon, thereby drastically reducing and, in some cases, virtually eliminating maintenance cleaning of compressors. The regular use of Omega 615 extends oil change intervals dramatically, reduces oil consumption and reduces repair frequencies, in direct relation to the operating costs of compressing equipment.

## INCOMPARABLE PERFORMANCE CHARACTERISTICS:

Omega 615 offers the highest level of operational efficiency possible of the current state-of-the-art level. Following is a brief comparison of some of this remarkable lubricant's capabilities:

	ORDINARY COMPRESSOR OIL	OMEGA 615 ULTRA-PERFORMANCE COMPRESSOR OIL
Maximum oil life in rotary-type compressors:	2,000 HRS (MAX)	8-10,000 HRS +
Typical pour point:	-20°C	-57°C
High temperature evaporation loss @205°C	10% approx.	<3%
Compatibility with mineral oils:	-	GOOD
Low volatility:	FAIR	Excellent
Effect on most paints & finishes:	Moderate	None
Hydrolytic stability: (Stability in presence of water)	Moderate	Excellent
Anti-rust properties:	Good	Excellent
Elastomer (seal) compatibility	Dependent on seal stock	Good

## ENGINEERED TO EXCEL:

Omega 615 will provide improved wear protection at high temperatures and yet, equally prevent deposit formation in low temperature systems, such as refrigeration compressors. Due to improved anti-oxidants and lubricity, Omega 615 will enhance compressor efficiency while reducing discharge valve deposits.

Due to its significantly higher oxidation stability, Omega 615 ISO VG 46 is especially suitable for use in rotary screw-and rotary vane-type compressors where the operational temperature usually exceeds 100-110°C and there is markedly excessive aeration, which causes rapid deterioration in the performance of ordinary compressor oils.

Omega 615 ISO VG 100 is recommended for conventional reciprocating-type compressors which require a higher viscosity oil for optimum performance.

Also, due to Omega 615's remarkable stability at ultra low temperatures, it will also outperform the best of the ordinary refrigeration compressor oils (which only perform down to their -40°C pour point), while Omega 615's pour point is -57°C.

## TYPICAL DATA:

TEST	ASTM TEST METHOD	TEST RESULT	
		ISO VG 46	ISO VG 100
Appearance	Visual	Off Color White	Off Color White
Density, Kg/L @ 15°C	D-1298	0.835	0.838
Viscosity, cSt @ 40°C	D-445	46	99
Viscosity, cSt @ 100°C	D-445	7.8	14.2
Viscosity, cSt @ -40°C		30000	82000
Viscosity Index	D-2270	138	147
Flash Point, COC °C(°F)	D-92	258(496)	264(507)
Pour Point, °C(°F)	D-97	-57(-71)	-45(-49)
Total Acid Number, mg KOH/g	D-974	0.7	0.7
Foaming Characteristics -			
All Sequences, After Settling	D-892	Nil	Nil
Rust Prevention Characteristics	D-665	Pass	Pass
Copper Strip Corrosion, 3 hours @ 100°C	D-130	1b	1b
Evaporation Loss -			
6.5 hrs @205°C, % Mass	D-972	3	2.7
Oxidation Characteristics -			
Hours to TAN 2.0	D-943	>3000	>2500
Carbon Residue, Conradson, % Mass	D-524	0.02	0.02

## APPLICATION:

Follow equipment manufacturers' filling and draining instructions. Omega 615 ISO VG 46 provides excellent service characteristics in flooded rotary compressors (vane-type and screw-type). The ISO VG 100 grade is engineered specially to provide improved performance for reciprocating-type air compressors. Oil life exceeds that of ordinary compressor oils by four hundred to five hundred percent!

# SAFETY DATA SHEET



Product name: Omega 615  
Supersedes date: 2016-05-10  
Product No.:

Page: 1/9  
Last revised date: 2019-08-20  
SDS-ID: GB-EN/7.0

## SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

### 1.1. Product identifier

Product name: Omega 615  
Container size: 5 l, 20 l

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Application: Lubricant.

### 1.3. Details of the supplier of the safety data sheet

Supplier: EU importer:

.  
.

Manufacturer: ITW PP & F Korea Limited.  
13th Fl., Unit B, PAX Tower  
609 Eonju-ro, Gangnam-gu  
Seoul, Korea 06108  
Tel:+82-2-2088-3560  
Fax:+82-2-513-3567  
magna@magnagroup.com  
www.magnagroup.com

### 1.4. Emergency telephone number

Emergency telephone: Call a Poison Center, emergency number or doctor/physician.

## SECTION 2: HAZARDS IDENTIFICATION

### 2.1. Classification of the substance or mixture

CLP: Not classified.

### 2.2. Label elements

The substance/mixture does not meet the criteria for classification and labelling.

### 2.3. Other hazards

PBT/vPvB: This product does not contain any PBT or vPvB substances.

Other: Prolonged or repeated contact with skin may cause redness, itching, irritation, eczema, skin cracking and oil acne.

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.2. Mixtures

The product contains: synthetic oils and additives.

All substances in the product are either registered or exempt from registration under REACH. Only classified substances above threshold limits or substances with an exposure limit are shown.

# SAFETY DATA SHEET

Product name:	Omega 615	Page:	2/9
Supersedes date:	2016-05-10	Last revised date:	2019-08-20
Product No.:		SDS-ID:	GB-EN/7.0

---

CLP:

<u>%:</u>	<u>CAS-No.:</u>	<u>EC No.:</u>	<u>REACH Reg. No.:</u>	<u>Chemical name:</u>	<u>Hazard classification:</u>	<u>Notes:</u>
60-100	68037-01-4	500-183-1	01-2119486452-34-0018	Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated	-	

## SECTION 4: FIRST AID MEASURES

### 4.1. Description of first aid measures

Inhalation: Move into fresh air and keep at rest. In case of persistent throat irritation or coughing or after inhalation of oil mist: Seek medical attention and bring along these instructions.

Skin contact: Remove contaminated clothing immediately and wash skin with soap and water. In case of rashes, wounds or other skin disorders: Seek medical attention and bring along these instructions.

Eye contact: Immediately flush with plenty of water for at least 15 minutes. Remove any contact lenses and open eyelids widely. If irritation persists: Seek medical attention and bring along these instructions.

Ingestion: Immediately rinse mouth and drink plenty of water. Keep person under observation. If person becomes uncomfortable seek hospital and bring these instructions.

### 4.2. Most important symptoms and effects, both acute and delayed

### 4.3. Indication of any immediate medical attention and special treatment needed

Medical attention/treatments: Treat symptomatically.

## SECTION 5: FIREFIGHTING MEASURES

### 5.1. Extinguishing media

Extinguishing media: Small fires: Extinguish with carbon dioxide or dry powder.  
Larger fires: Extinguish with foam, carbon dioxide or dry powder.  
Do not use water jet as an extinguisher, as this will spread the fire.

### 5.2. Special hazards arising from the substance or mixture

Specific hazards: During fire, gases hazardous to health may be formed.

### 5.3. Advice for firefighters

Protective equipment for fire-fighters: Selection of respiratory protection for fire fighting: follow the general fire precautions indicated in the workplace.

---

# SAFETY DATA SHEET

Product name:	Omega 615	Page:	3/9
Supersedes date:	2016-05-10	Last revised date:	2019-08-20
Product No.:		SDS-ID:	GB-EN/7.0

---

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### **6.1. Personal precautions, protective equipment and emergency procedures**

Personal precautions: Avoid inhalation of oil mist and contact with skin and eyes. Follow precautions for safe handling described in this safety data sheet.

### **6.2. Environmental precautions**

Environmental precautions: Do not discharge into drains, water courses or onto the ground.

### **6.3. Methods and material for containment and cleaning up**

Methods for cleaning up: Absorb spillage with oil-absorbing material. Clean contaminated area with oil-removing material.

### **6.4. Reference to other sections**

References: For personal protection, see section 8.

## SECTION 7: HANDLING AND STORAGE

### **7.1. Precautions for safe handling**

Safe handling advice: Observe good chemical hygiene practices. Avoid prolonged and repeated contact with oil, particularly used oil. Always remove oil with soap and water or skin cleaning agent, never use organic solvents. Do not use oil-contaminated clothing or shoes, and do not put rags moistened with oil into pockets.

Technical measures: Use work methods which minimise oil mist production.

Technical precautions: When working with heated oil, mechanical ventilation may be required.

### **7.2. Conditions for safe storage, including any incompatibilities**

Technical measures for safe storage: No special precautions.

Storage conditions: Store in tightly closed original container.

### **7.3. Specific end use(s)**

Specific use(s): Lubricant.

---

# SAFETY DATA SHEET

Product name:	Omega 615	Page:	4/9
Supersedes date:	2016-05-10	Last revised date:	2019-08-20
Product No.:		SDS-ID:	GB-EN/7.0

---

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### **8.1. Control parameters**

No occupational exposure limit assigned.

### **8.2. Exposure controls**

<u>Engineering measures:</u>	Provide adequate ventilation and minimise the risk of inhalation of vapours and oil mist. Provide access to washing facilities incl. soap, skin cleanser and fatty cream.
<u>Personal protection:</u>	Personal protection equipment should be chosen according to the relevant standards and in discussion with the supplier of the personal protective equipment.
<u>Respiratory equipment:</u>	In case of inadequate ventilation or risk of inhalation of oil mist, suitable respiratory equipment with combination filter (type A2/P3) can be used.
<u>Hand protection:</u>	Risk of contact: Wear protective gloves. The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material.
<u>Eye protection:</u>	Risk of contact: Wear goggles/face shield.
<u>Skin protection:</u>	Wear apron or protective clothing in case of splashes.
<u>Hygiene measures:</u>	Wash hands after contact. Wash contaminated clothing before reuse.
<u>Environmental Exposure Controls:</u>	Not available.

---

# SAFETY DATA SHEET

Product name: Omega 615  
Supersedes date: 2016-05-10  
Product No.:

Page: 5/9  
Last revised date: 2019-08-20  
SDS-ID: GB-EN/7.0

---

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

Appearance: Clear liquid.  
Odour: Almost odourless.  
Odour threshold: Not available.  
pH: Not available.  
Melting point / freezing point: Not available.  
Boiling point: Not available.  
Flash point: > 200°C  
Evaporation rate: Not available.  
Explosive limits Not available.  
Vapour pressure: Not available.  
Vapour density: Not available.  
Relative density: ~ 0,85  
Solubility: Immiscible with water.  
Partition coefficient (n-octanol/water): Not available.  
Auto-ignition temperature (°C): Not available.  
Decomposition temperature (°C): Not available.  
Viscosity: Not available.  
Explosive properties: Not available.  
Oxidising properties: Not available.

### 9.2. Other information

Other data: Kinematic viscosity: ~ 100 mm<sup>2</sup>/s (40 °C)

---



# SAFETY DATA SHEET

Product name:	Omega 615	Page:	6/9
Supersedes date:	2016-05-10	Last revised date:	2019-08-20
Product No.:		SDS-ID:	GB-EN/7.0

---

## SECTION 10: STABILITY AND REACTIVITY

### 10.1. Reactivity

Reactivity: Not reactive.

### 10.2. Chemical stability

Stability: Stable under normal temperature conditions.

### 10.3. Possibility of hazardous reactions

### 10.4. Conditions to avoid

Conditions to avoid Heat, sparks, flames.

### 10.5. Incompatible materials

Incompatible materials: Strong oxidising substances.

### 10.6. Hazardous decomposition products

Hazardous decomposition products: None known.

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1. Information on toxicological effects

The harmful effects may increase in used oil.

Acute Toxicity (Oral): Based on available data, the classification criteria are not met.

Acute Toxicity (Dermal): Based on available data, the classification criteria are not met.

Acute Toxicity (Inhalation): Based on available data, the classification criteria are not met.

Skin Corrosion/Irritation: Based on available data, the classification criteria are not met.

Serious eye damage/irritation: Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation: Based on available data, the classification criteria are not met.

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive Toxicity: Based on available data, the classification criteria are not met.

STOT - Single exposure: Based on available data, the classification criteria are not met.

STOT - Repeated exposure: Based on available data, the classification criteria are not met.

Aspiration hazard: Based on available data, the classification criteria are not met.

Inhalation: Inhalation of oil mist or vapours formed during heating of the product will irritate the respiratory system and provoke coughing.

Skin contact: Degreasing. Prolonged or frequent contact may cause redness, itching, eczema and skin cracking.

Eye contact: Splashes may irritate.

Ingestion: May irritate and cause malaise.

Specific effects: Prolonged or repeated contact with used oil may cause serious skin diseases, such as dermatitis.

---

# SAFETY DATA SHEET

Product name:	Omega 615	Page:	7/9
Supersedes date:	2016-05-10	Last revised date:	2019-08-20
Product No.:		SDS-ID:	GB-EN/7.0

---

## SECTION 12: ECOLOGICAL INFORMATION

### **12.1. Toxicity**

Ecotoxicity: Oil spills are generally hazardous to the environment.

### **12.2. Persistence and degradability**

Degradability: The product is slowly degradable.

### **12.3. Bioaccumulative potential**

Bioaccumulative potential: No data available on bioaccumulation.

### **12.4. Mobility in soil**

Mobility: No data available.

### **12.5. Results of PBT and vPvB assessment**

PBT/vPvB: This product does not contain any PBT or vPvB substances.

### **12.6. Other adverse effects**

Other adverse effects: None known.

## SECTION 13: DISPOSAL CONSIDERATIONS

### **13.1. Waste treatment methods**

Dispose of waste and residues in accordance with local authority requirements. Waste is classified as hazardous waste.

Waste from residues: EWC-code: 13 02 06

---

# SAFETY DATA SHEET

Product name:	Omega 615	Page:	8/9
Supersedes date:	2016-05-10	Last revised date:	2019-08-20
Product No.:		SDS-ID:	GB-EN/7.0

---

## SECTION 14: TRANSPORT INFORMATION

The product is not covered by international regulation on the transport of dangerous goods (IMDG, IATA, ADR/RID).

### **14.1. UN number**

UN-No: -

### **14.2. UN proper shipping name**

Proper Shipping Name: -

### **14.3. Transport hazard class(es)**

Class: -

### **14.4. Packing group**

PG: -

### **14.5. Environmental hazards**

Marine pollutant: -

Environmentally Hazardous substance: -

### **14.6. Special precautions for user**

Special precautions: None known.

### **14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code**

Transport in bulk: Not relevant.

## SECTION 15: REGULATORY INFORMATION

### **15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

National regulation: Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, with amendments.  
Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments.  
The Control of Substances Hazardous to Health Regulations 2002 (S.I. 2002 No. 2677) with amendments.  
EH40/2005, Workplace exposure limits 2005, with amendments.  
The List of Wastes (England) (Amendment) Regulations 2005. (SI 2005 No. 895).

### **15.2. Chemical Safety Assessment**

CSA status: No chemical safety assessment has been carried out.

---

# SAFETY DATA SHEET

Product name:	Omega 615	Page:	9/9
Supersedes date:	2016-05-10	Last revised date:	2019-08-20
Product No.:		SDS-ID:	GB-EN/7.0

---

## SECTION 16: OTHER INFORMATION

The user must be instructed in the proper work procedure and be familiar with the contents of these instructions.

Handling of used oils:

Protect health - avoid prolonged and repeated skin contact. Wash with soap and water. Protect the environment - do not pollute drains, water courses or the soil. Contact your local authority for any used oil disposal instructions.

The following sections contain revisions or new statements: 2, 3, 8, 9, 12, 14, 15, 16.

Omega Manufacturing Division  
13th floor, Unit B, PAX Tower, 609 Eonju-ro,  
Gangnam-Gu, Seoul, Korea 06108  
Tel : +82-2-2088-3560  
Fax : +82-2-513-3567  
Web site : [www.magnagroup.com](http://www.magnagroup.com)

The Omega Trade Mark is the property of ITW, Inc., and is used under license by ITW PP & F Korea Limited.

### Abbreviations and acronyms

used in the safety data sheet: PBT = Persistent, Bioaccumulative and Toxic.  
vPvB = very Persistent and very Bioaccumulative.

Additional information: Classification according to Regulation (EC) No. 1272/2008: Calculation method.

---

The information on this data sheet represents our current data and is reliable provided that the product is used under the prescribed conditions and in accordance with the application specified on the packaging and/or in the technical guidance literature. Any other use of the product which involves using the product in combination with any other product or any other process is the responsibility of the user.

Made by DHI - Environment and Toxicology, Agern Allé 5, DK-2970 Hørsholm, Denmark.  
[www.dhigroup.com](http://www.dhigroup.com).

---