

# RUBIA XT

15W-40



TOTAL

**Multigrade oil for diesel engine**

## UTILISATION

- Developed for all Diesel engines, turbocharged or not, in severe service conditions in all seasons.
- Suited for extended drain intervals (up to 30 000 km according to manufacturers).

## PERFORMANCES

### Specifications

ACEA E2  
API CF-4/SJ

### OEMS' approvals

DAIMLER CHRYSLER MB page 228.1  
MAN 271  
VOLVO VDS  
CATERPILLAR TO-2  
MIL-L 2104 E

## CUSTOMER BENEFITS

### Performances techniques

- Multigrade
- Very high viscosity index
- Excellent viscosity stability in operation
- Excellent detergency level
- High dispersancy level
- Excellent antiwear and anticorrosion properties
- Very good anti oxydant, antirust and antifoam properties.

## CHARACTERISTICS

	Units	SAE grade <b>15W-40</b>
Volumetric mass at 15°C	kg/m <sup>3</sup>	887
Viscosity at 100°C	mm <sup>2</sup> /s	13.9
Viscosity index	-	131
Flash Point	°C	>200
Pour point	°C	-30
T.B.N	mgKOH/g	9.2

*The typical characteristics mentioned represent mean values.*

TOTAL LUBRIFIANTS  
16, rue de la République  
F-92800 PUTEAUX

RUBIA XT 15W-40  
February 2005  
N° MPR/02/05



This lubricant, when used according to our recommendations and for the purpose for which it is intended, presents no particular hazards. A safety data sheet complying with current EC legislation can be obtained from your local commercial adviser.